

XTRA FLEX-WP

Water Based Flexographic Ink Cleaner

Cleans water based standard ink, UV ink, coatings, residues and contaminants away from anilox roller cells, flexo plates and press parts.

- Can be diluted with 50% water.
- Removes coatings and varnishes from a variety of surfaces.
- A Low VOC Wash.
- Use as a manual or auto wash for/in (Anilox-Plate-Ultrasonic-Parts).
- General purpose shop cleaner: Cement floors, rugs, rubber mats and parts wash.
- Non-Flammable.

Direction For Use:

Anilox Manual Wash:

Apply onto anilox roller using a brush or shop towel to scrub and remove ink pigments, coatings and residues.

Parts Manual Wash:

Spray or immerse part(s) 1-25 minutes. Remove parts from the cleaner. Quickly, use a plastic or brass brush to gently scrub stubborn contaminants loose. Rinse the parts in water, let air dry, or dry with a shop towel.

*See note on aluminum or aluminum alloy parts.

Ultrasonic Bath/Soak Tank:

Utilizing existing time/cycle settings: Apply full strength or dilute 1:4 parts water to determine cleaning strength and results desired.

Specifications:

VOC content lb. / gallon	0.9
VOC content grams / liter	113
Flashpoint	None
Color	Orange
CA. Compliant	Yes



Floors & Walls:

Spray surface directly or dilute with water to determine desired cleaning strength. Clean area with mop, brush or squeegee. Final rinse with water.

IMPORTANT: As with all washes, pre-test for compatibility prior to applying onto any surface, substrate, part or general area.

Read sds before use.

Available In:

Product Code	Unit	Case Qty.
027120D	1 Gallon (3.785 ltr)	4
027120E	5 Gallons (18.9 ltr)	Each
027120G	55 Gallons (208 ltr)	Each

