

V-SUB

Alcohol Replacement Fountain Additive

V-SUB is used successfully by many world wide. It provides an excellent overall balance between the wetting and viscosity needed to successfully replace alcohol and keep water settings at a minimum. Add it to any fountain solution for a total replacement of alcohol. V-SUB reduces the surface dynamic tension of water to the 30s.

- Low Dosage.
- Reduces piling.
- Usable with all fountain solutions.
- Reduces surface tension to the low 30s.
- Allows wide latitude of wetting.
- For use on sheet-fed or web equipment.

Direction For Use:

Recommended dosage range - 2 oz. to 4 oz. per gallon. We recommend starting with 3 oz. / gallon. Once running, adjust dosage up or down as needed.



Recommended dosage range 1.5% to 3%. We recommend starting with 2.5 %, adjusting dosage up or down as needed.

Specifications:

| | |
|---------------------------|-----------|
| VOC content lb. / gallon | 6.1 |
| VOC content grams / liter | 731 |
| Flashpoint | > 180°F |
| Color | Colorless |
| CA. Compliant | Yes |

Available In:

| Product Code | Unit | Case Qty. |
|--------------|----------------------|-----------|
| 026070D | 1 Gallon (3.785 ltr) | 4 |
| 026070E | 5 Gallons (18.9 ltr) | Each |
| 026070G | 55 Gallons (208 ltr) | Each |
| | | |
| | | |

